

Effect of Heat Transfer through the Cylinder Wall on Performance of an Air-Standard Otto Cycle

Syed Yousufuddin

Department of Mechanical Engineering
Jubail University College, Royal Commission for Jubail & Yanbu
Jubail Industrial City- 31961, P.O. Box 10074, Kingdom of Saudi Arabia
syedyousufuddin@rediffmail.com

Abstract — Exergy efficiency (also known as the second-law efficiency or rational efficiency) computes the efficiency of a process taking the second law of thermodynamics into account. It is described as the ratio of the actual thermal efficiency (first-law efficiency) to the maximum possible (reversible) thermal efficiency under the same conditions. In this paper, the second-law efficiency of an air-standard Otto cycle with consideration of heat losses is analyzed, using finite-time thermodynamics. Moreover, effects of various design parameters such as the initial temperature of the working fluid and the constants related to combustion and heat transfer through the cylinder wall, on variation curve of the second-law efficiency versus first-law efficiency are indicated. The obtained results of this paper can be useful for the analysis and comparison of real engines.

Keywords—Finite-time thermodynamics; Air-standard Otto cycle; Heat loss; First-law efficiency; Second-law efficiency

I. INTRODUCTION

The Otto cycle is one of the types of air-standard cycles; also is an ideal cycle for internal combustion engines. The second-law efficiency is the ratio of the actual thermal efficiency (first-law efficiency) to the maximum possible (reversible) thermal efficiency under the same conditions [1]. For the work-producing devices, the second-law efficiency can also be expressed as the ratio of the useful work output and the maximum possible (reversible) work output [1, 2]. In recent years, many attentions have been paid in order to analyzing the performances of the Otto cycle and exergy analysis for it. Effects of heat loss as percentage of fuel's energy, friction and variable specific heats of working fluid on performance of air standard Otto cycle are investigated by Lin *et al.* [3]. Finite-time thermodynamic modeling and analysis of an irreversible Otto cycle is done by Ge *et al.* [4]. Heat transfer effects on the net work output and efficiency characteristics for an air-standard Otto cycle is studied by Chen *et al.* [5]. Thermodynamic simulation of performance of an Otto cycle with heat transfer and variable specific heats of working fluid performed by Ge *et al.* [6] and performance analysis of an Irreversible Otto Cycle using Finite Time Thermodynamics is done by Mehta *et al.* [7]. In this

paper, the second-law analysis of an air-standard Otto cycle with heat transfer is investigated.

II. THERMODYNAMIC ANALYSIS

The T - s diagram for an air-standard Otto cycle is shown in figure 1. The Otto cycle consists of four processes; isentropic compression (1→2), constant-volume heat addition (2→3), isentropic expansion (3→4) and constant-volume heat rejection (4→1). For an ideal air-standard Otto cycle, the heat added per unit mass of the working fluid during the constant-volume process (2→3) is defined as:

$$q_{in} = C_v (T_3 - T_2), \quad (1)$$

Where, C_v is the constant-volume specific heat. The temperatures within the combustion chamber of an internal combustion engine reach values on the order of 2700 (K) and up. Materials in the engine cannot tolerate this kind of temperature and would quickly fail if proper heat transfer did not occur. Thus, because of keeping an engine and engine lubricant from thermal failure, the interior maximum temperature of the combustion chamber must be limited to much lower values by heat fluxes through the cylinder wall during the combustion period. Since, during the other processes of the operating cycle, the heat flux is essentially quite small and negligible due to the very short time involved for the processes, it is assumed that the heat loss through the cylinder wall occurs only during combustion. The calculation of actual heat transfer through the cylinder wall occurring during combustion is quite complicated, so it is approximately assumed to be proportional to the average temperature of both the working fluid and cylinder wall and that, during the operation, the wall temperature remains approximately invariant. The heat added per unit mass of the working fluid of the cycle by combustion is given by the following linear relation [6]:

$$q_{in} = A - B(T_2 + T_3), \quad (2)$$

Where, A and B are two constants related to the combustion and the heat transfer, respectively. Parameter A is the total heat energy of the fuel and parameter B is the waste energy by heat loss. Combining equations (1) and (2) yields:

$$T_3 = \frac{[A + (C_v - B)T_2]}{(C_v + B)} \quad (3)$$




Fig. 1 The T-s diagram of air-standard Otto cycle [1]

For the isentropic processes (1→2) and (3→4), we have:

$$T_2 = T_1 r^{k-1}, \quad (4)$$

$$\text{And } T_3 = T_4 r^{k-1}, \quad (5)$$

Where, r is the compression ratio, (V_1/V_2), and k is the specific heat ratio (C_p/C_v). For the air-standard Otto cycle, the heat rejected per unit mass of the working fluid during the constant-volume process (4→1) is defined as:

$$q_{out} = C_v (T_4 - T_1). \quad (6)$$

The net work output per unit mass of the working fluid for the Otto cycle is given by the following equation:

$$w_{net} = q_{in} - q_{out} = C_v (T_3 - T_2) - C_v (T_4 - T_1), \quad (7)$$

Where, T_1 , T_2 , T_3 and T_4 are absolute temperatures at states 1, 2, 3 and 4. By substituting equations (3), (4) and (5) into equations (1) and (7), the first-law efficiency (η_I) of the Otto cycle will be obtained as:

$$\eta_I = \frac{w_{net}}{q_{in}} = 1 - r^{k-1}. \quad (8)$$

According to References [1, 2], the second-law

efficiency (η_{II}) of a system is defined as:

$$\eta_{II} = \frac{w_{net}}{w_{max}}, \quad (9)$$

where, w_{max} is the maximum possible work that the system can produce which is defined as:

$$w_{max} = \eta_{max} \cdot q_{in}, \quad (10)$$

where, η_{max} is the maximum possible thermal efficiency (Carnot's efficiency) which is defined as following:

$$\eta_{max} = \left(1 - \frac{T_1}{T_3}\right). \quad (11)$$

Substituting equations (1) and (11) into equation (10) gives:

$$w_{max} = C_v (T_3 - T_2) \left(1 - \frac{T_1}{T_3}\right). \quad (12)$$

Finally, by some simple algebraic calculations, w_{net} , w_{max} and η_{II} will be obtained as follows:

$$w_{net} = \eta_I \cdot q_{in} = \frac{C_v \eta_I [A - 2BT_1 / (1 - \eta_I)]}{(C_v + B)}, \quad (13)$$

and

$$w_{max} = C_v \left[\frac{A(1 - \eta_I) - 2BT_1}{(1 - \eta_I)(C_v + B)} \right] \times \left[\frac{A(1 - \eta_I) + \eta_I(C_v + B)T_1 - 2BT_1}{A(1 - \eta_I) + (C_v - B)T_1} \right], \quad (14)$$

and

$$\eta_{II} = \frac{\eta_I [A(1 - \eta_I) + (C_v - B)T_1]}{A(1 - \eta_I) + \eta_I(C_v + B)T_1 - 2BT_1}. \quad (15)$$

III. RESULTS AND DISCUSSIONS

In this paper, the following parameters are used: $A = 3000 \rightarrow 4500$ (kJ/kg.K), $B = 0.5 \rightarrow 1.3$ (kJ/kg.K), $k = 1.35$, $T_1 = 280 \rightarrow 370$ (K). Figure 2 shows the effects of parameters A , B and T_1 on the second-law efficiency for a fixed value of the first-law efficiency. Based on this figure, the second-law efficiency increases, with decreasing A , and increasing B and T_1 . Figures 3, 4 and 5 indicate effects of parameters A , B and T_1 on variation curve of the second-law efficiency versus the first-law efficiency. It can be seen that the first and second law efficiencies increase with increasing the compression ratio, r . Moreover, it is

found that, for a given compression ratio, the second-law efficiency increases, with the decrease of A , and the increase of B and T_1 . This means that, for these variations, the maximum possible thermal efficiency will decrease that, finally, cause slope of above curve to increase. It can be seen that, the results of the figure 2, are confirmed by figures 3, 4 and 5. Note that some values of the second-law efficiency might be insufficient for a feasible Otto cycle.




Fig. 2 Effect of A and B on the $\eta_{II} - T_1$ characteristics




Fig. 3 Effect of A on the $\eta_{II} - \eta_I$ characteristics




Fig. 4 Effect of B on the $\eta_{II} - \eta_I$ characteristics




Fig. 5 Effect of T_1 on the $\eta_{II} - \eta_I$ characteristics

IV. CONCLUSIONS

In this paper, the effect of heat transfer through the cylinder wall on performance of an air-standard Otto cycle has been investigated, using first and second-law efficiencies. The results show that the effect of the heat transfer loss on performance of the cycle is obvious, and they should be considered in practical cycle analysis. The finding in this paper may provide significant guidance for the design of practice internal combustion engines and improvements of real reciprocating engines.

REFERENCES

- [1] Cengel, Y.A. and Boles, M.A., "Thermodynamics: an Engineering Approach", 7th Ed, McGraw-Hill Book Company, (2016).
- [2] Bejan, A., "Advanced Engineering Thermodynamics", Hoboken, New Jersey: John Wiley & Sons INC, (2008).
- [3] Lin, J.C. and Hou, S.S., "Effects of Heat Loss as Percentage of Fuel's Energy, Friction and Variable Specific Heats of Working Fluid on Performance of Air Standard Otto Cycle", Energy Conversion and Management, Vol. 49, No. 5, (2008), 1218–1227.
- [4] Ge, Y., Chen, L. and Sun, F., "Finite-Time Thermodynamic Modelling and Analysis of an Irreversible Otto Cycle", Applied Energy, Vol. 85, No. 7, (2008), 618–624.
- [5] Chen, L., Wu, C., Sun, F. and Cao, S., "Heat Transfer Effects on the Net Work Output and Efficiency Characteristics for an Air-Standard Otto Cycle", Energy Conversion and Management, Vol. 39, No. 7, (1998), 643-648.
- [6] Ge, Y., Chen, L., Sun, F. and Wu, C., "Thermodynamic Simulation of Performance of an Otto Cycle with Heat Transfer and Variable Specific

Heats of Working Fluid”, International Journal of Thermal Sciences, Vol. 44, No. 5, (2005), 506–511.

[7] Mehta, H.B. and Bharti, O.S., “Performance Analysis of an Irreversible Otto Cycle using Finite Time Thermodynamics”, Proceedings of the World Congress on Engineering, Vol II ,WCE 2009, July 1 - 3, London, U.K, (2009).

[8] Calam A., Solmaz H., Uyumaz A., Polat S., Yilmaz E and İçingür Y., “Investigation of usability of the fusel oil in a single cylinder spark ignition engine”, J. Energy Ins., 88(3): 258-265, (2015).

[9] Wu C., Deng K. and Wang Z., “The effect of combustion chamber shape on cylinder flow and lean combustion process in a large bore spark-ignition CNG engine”, J. Energy Ins., 89(2): 240-247, (2016).

[10] Gonca G., Sahin B., Ust Y. and Parlak A., “Comprehensive performance analyses and optimization of the irreversible thermodynamic cycle engines (TCE) under maximum power (MP) and

maximum power density (MPD) conditions”, Appl. Therm. Eng. 85: 9-20, (2015).

[11] Bagirov H., Can I., Oner C., Sugoza I. and Kapicioglu A., “Experimental investigation the effects of mixture impoverished on the specific fuel consumption, engine performance and exhaust emissions a pre-combustion chamber gasoline engine”, J. Energy Ins., 88(3): 205208, (2015).

[12] Najjar Y. S. H. and Amer M. M. B., “Using a smart device and neuro-fuzzy control system as a sustainable initiative with green cars”, J. Energy Ins., 89(2): 256-263, (2016).

[13] Gonca G., Sahin B., Ust Y. and Parlak A., “A Study on Late Intake Valve Closing Miller Cycled Diesel Engine”, Arab. J. Sci. Eng., 38: 383-293, (2013).